

## Valve stem seals

Provide a defined metering rate of oil to the valve stem interface of internal combustion engines, while ensuring low engine emissions and competitive pricing.

### Available applications

Diesel and gasoline engines with and without turbo chargers.

### SKF offers two basic designs of state-of-the-art valve stem seals:

- Non-integrated seal (Type 861+866), which fulfils the function of oil metering rate
- Integrated seal (Type 863), which additionally incorporates a spring seat to prevent wear on the cylinder head

SKF is in a position to finely tune the design of seals to provide the optimum oil metering rate for the application.

# Superior product materials, SKF formulated fluorpolymers, are used in the manufacturing of the valve stem seals resulting in:

- Excellent chemical resistance
- Excellent temperature resistance
- High reliability
- Low wear

# The design characteristics of the valve stem seals allow for dynamic sealing abilities such as:

- Flexible lip to allow valve stem movement and static eccentricity
- Lip stabilization by bonded reinforced ring
- Constant radial force by tempered garter spring

## With SKF, you get a truly effective product with the following advantages:

- Consistent oil metering and long life
- Developed to specific customer requirements or use of standard seals
- Fully automated production cells mean top quality
- Complete technical service to provide optimal function
- Long-term emissions control
- Competitive pricing





Non-integrated types



Integrated type

#### skf.com

® SKF is a registered trademark of the SKF Group.

© SKF Group 2019

The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.

PUB SE/P8 06733/2 EN · June 2019

For further information, please contact: seals.automotive@skf.com